Citation for published version:

Wung, N, Acott, SM, Tosh, D & Ellis, MJ 2014, 'Hollow fibre membrane bioreactors for tissue engineering applications', *Biotechnology Letters*, vol. 36, no. 12, pp. 2357-2366. <https://doi.org/10.1007/s10529-014-1619-x>

DOI:

[10.1007/s10529-014-1619-x](https://doi.org/10.1007/s10529-014-1619-x)

Publication date:

2014

Document Version

Peer reviewed version

[Link to publication](#)

University of Bath

Alternative formats

If you require this document in an alternative format, please contact:
openaccess@bath.ac.uk

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

Take down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Hollow Fibre Membrane Bioreactors for Tissue Engineering Applications

Nelly Wung,^{a,b} Samuel M. Acott,^a David Tosh^b and Marianne J. Ellis ^{*,a}

^a Centre for Regenerative Medicine, Department of Chemical Engineering, University of Bath, Bath, BA2 7AY, UK. Tel: +44 (0) 1225 384484

^b Centre for Regenerative Medicine, Department of Biology & Biochemistry, University of Bath, Bath, BA2 7AY, UK.

*E-mail: M.J.Ellis @bath.ac.uk

*Tel: +44 (0) 1225 384484

Abstract

Hollow fibre membrane bioreactors (HFB) provide a novel approach towards tissue engineering applications in the field of regenerative medicine. For adherent cell types HFBs offer an *in vivo*-like microenvironment as each fibre replicates a blood capillary and mass transfer rate across the wall is independent from the shear stresses experienced by the cell. HFB also possesses the highest surface area to volume ratio of all bioreactor configurations. In theory these factors enable a high quantity of the desired cellular product with less population variation, and favourable operating costs. Experimental analyses of different cell types and bioreactor designs show encouraging steps towards producing a clinically relevant device. This review discusses the basic HFB design for cell expansion and *in vitro* models; compares data produced on commercially available systems and addresses the operational differences between theory and practice. HFBs are showing some potential for mammalian cell culture but further work is needed to fully understand the complexities of cell culture in HFBs and how best to achieve the high theoretical cell yields.

KEYWORDS *bioprocessing; bioreactor; cell therapies; hollow fibre membrane; in vitro; scale up; tissue engineering*

Introduction

The requirement to culture mammalian cells in large quantities and in an *in vivo*-like environment has led to the application of a wide range of different bioreactor configurations based on traditional biochemical engineering designs. One bioreactor type that is showing promise is the hollow fibre membrane bioreactor (HFB); this configuration has been applied across all tissue engineering applications (TE-apps), i.e. cell expansion for regenerative medicine (Gundersen et al. 2010; Nold et al. 2013; Roberts et al. 2012), cell-scaffold constructs for regenerative medicine from injectable cell-gel composites (Seliktar 2012; Shin et al. 2013; Vermonden et al. 2012) and large bone defect augmentation (Niemeyer et al. 2010; Soardi et al. 2011; Torres et al. 2011), to cell delivery after myocardial infarction (Bernstein and Srivastava 2012; Roberts et al. 2012; Usuludin et al. 2012); and bioartificial organs (Oh et al. 2010; Oo et al. 2011); *in vitro*/toxicology models (Usuludin et al. 2012; Zhang et al. 2012), and most recently cultured meat, in the author's lab.

Relatively simple scale-up is theoretically possible with HFBs, compared to other bioreactor configurations, as scale-up can be based on Krogh cylinder modelling. The current trend for companies utilising TE-apps, when developing high quality cost effective bioprocesses, is to incorporate stirred tank bioreactors, which are traditionally and successfully used for the large-scale production of biopharmaceuticals. Despite the sensible lateral application of this configuration to TE-apps, the complexity of tissues and the sensitivity of mammalian cells to subtle changes to their environment has driven the design of a second generation of bioreactors to meet the biological, financial and regulatory requirements to enable mass-production to meet global demands.

Given the breadth of TE-apps where the final product from a cell expansion process will range from undifferentiated stem cells to a tissue-like cell-scaffold construct, it is unlikely there will be a single bioreactor type that exhibits broad utility, as the stirred tank has done for biopharmaceutics. Not only will the cell type(s) and required extent of differentiation vary, but so will the downstream processing step of removing the product, purifying it and packaging it for delivery and application in the clinic. As such HFBs are not suited to all tissues and all applications and the tissue engineer should choose the bioreactor configuration only once the product is fully understood. Herein HFBs are reviewed in

the context of the applications for which they are particularly suited – as devices for cell expansion and as *in vitro* models.

HFBs for Regenerative Medicine Applications

The versatility of the HFB is owed to the ease at which environmental changes can be applied to the system. For example if used as a device for cell expansion the researcher would focus on applying the optimum conditions to accelerate rates of cell growth and cell number. Other practical considerations include the removal and extraction of the cells from the bioreactor once the desired number of cells is met. For a regenerative medicine construct, multiple cell types may be used (particularly when modelling heterogeneous tissues), and the fibres may be used to deliver drugs or growth factors to improve endogenous tissue regeneration. Cells can be cultured on the internal or external surfaces of the hollow fibre, as well as be suspended in a gel in the extracapillary space (ECS) (Figure 1).

FIGURE 1 PLACED HERE

HFBs for cell expansion

Given their design, HFBs have the potential to expand a population of cells to a clinically significant number and enable the differentiation of stem cells along desired lineages. These properties make HFBs an attractive prospect for regenerative medicine. To support this statement, a variety of cell types have already been successfully expanded (Table 1) and differentiated (Table 2) using the HFB system.

TABLE 1 AND TABLE 2 PLACED HERE

Several methods are available for determining the efficacy of cellular expansion. These methods include (i) direct quantification of seeding and harvesting cell numbers or densities (ii) indirectly quantifying by comparing changes in DNA, glucose or lactate concentrations over time or (iii) qualitatively depicting changes through imaging. These methods are not entirely comparable,

particularly where the result has not been quantified. Therefore, it is not possible to directly determine differences in efficacy between various experimental systems in the literature. A standardised direct quantitative method of cell growth alongside supplementary methods of determining cellular expansion would allow for efficient comparisons between HFB setups.

While the HFB system could potentially generate a renewable cell source at therapeutically significant levels, problems with producing clinically useful cells include maintaining population heterogeneity during the culture process (Williams et al. 2012) and the requirement of having to produce yields approximating 10^5 to 10^{13} cells per dose (Simaria et al. 2014). Therefore, it is important to identify how bioreactor design, culture conditions and scale-up can be improved to achieve the standards required for therapeutic use.

HFBs for regenerative medicine constructs

A three dimensional (3D) culture scaffold wherein the HFB contains a gel or cells cultured on hollow fibres are assembled sufficiently close to allow bridging holds a number of advantages over traditional two dimensional (2D) cultures grown in tissue culture flasks. 3D culture substrates are able to better represent the *in vivo* environment such that cell phenotype, gene expression and function are improved compared to the 2D environment; this is due to complex cellular interactions that occur between cells and the extracellular matrix (ECM) (Sun et al. 2006; Zhou et al. 2008).

Cells can be cultured on the intraluminal wall of hollow fibre membranes. This has been demonstrated with alveolar epithelial cells, where an air-liquid interface similar to that in lung tissue was reproduced by passing air through the fibre lumen (Grek et al. 2009). Endothelial cells constitute the inner surface of the vasculature. While they do not form tight junctions under 2D culture conditions, when cultured on the lumen surface and exposed to the shear stresses of media flow through the lumen, (similar to the flow of blood in vessels) they behave in a similar fashion to that seen *in vivo* (Ott and Ballermann 1995). The issue with this approach is that the mass transfer rate to the cells in

the ECS is now coupled to the shear stress experienced by the endothelial cells which may limit the feed flow rates used. Yamazoe and Iwata (2006) showed that culturing cells within the fibre lumen could potentially protect the cells from rejection by the host immune system if they were implanted into a patient, due to the ability to control the molecular weight cut off of the semipermeable membrane.

HFBs for use as *in vitro* models

In vitro models allow for the study of tissue function, as well as drug discovery and toxicology testing, and metabolism analysis without the need for using animal models; the same considerations can be applied to bioartificial organs but these are not reviewed here in detail. The HFB setup has been utilised in bioartificial organ design to replicate liver (Gautier et al. 2009) and kidney functions (Oo et al. 2011) with the intent of utilisation as clinical therapy. In the case of drug and toxicology testing, repeated dosage, acute and chronic effects may be examined depending on how long the model is maintained (Zeilinger et al. 2011). However, there are certain considerations associated with creating a system that is able to replicate the *in vivo* setting successfully, such as the interactions between different cell types and culture conditions that exactly match those found *in vivo* so that accurate extrapolation of data can be made. Furthermore, high cell growth rates may not be desirable once the cells have formed the model construct, instead requiring conditions that facilitate the desired cell number at a stationary phase but not their growth phase.

Physical control of the environment is relatively easy as the membrane characteristics, flow rates and mass transfer rates can be prescribed, however the biological environment in terms of the culture media is also of importance but is very complex. Basic culture medium conditions provide cells with the nutrients and growth factors specific to their environment to thrive. The medium can be further supplemented with growth factors and cytokines to aid proliferation and differentiation depending on

the requirements. pH may be controlled through the addition of an appropriate buffer or by careful assessment in media containing the indicator phenol red. Foetal bovine serum can also be added to the culture medium to allow deposition of surface proteins, aiding attachment of adherent cultures. The addition of antibiotics and antifungals can reduce the likelihood of infection within the closed system of the bioreactor. However, artificial culture media do not necessarily provide an exact replica of the types of nutrients (and the appropriate concentration) and gas seen physiologically which could affect cellular functions.

Whole blood has been utilised in HFB as the culture medium equivalent to *in vivo* conditions, to provide both nutrients and oxygenation to the cells whilst removing waste products. This route has drawbacks due to a lack of a supply of constant comparable blood, strict regulations for safe use, fouling by blood cell attachment to the membrane, and clotting. A compromise is to separate the red blood cells from whole blood and use them to supplement the chosen culture medium, thus preventing immune responses (Gundersen et al. 2010; Sullivan et al. 2007) or to add an anticoagulant to the system, either in the medium or coating the intraluminal surface to reduce thrombogenicity (Zhang et al. 2012). A study by Chen and Palmer (2010) added bovine haemoglobin to the culture medium in a HFB to act as an oxygen carrier. This showed a higher cell mass, improved efficiency of hepatocyte metabolism and drug detoxification, and conservation of albumin synthesis, and ammonia detoxifying functions compared to controls. Oxygen requirements vary between cell types, for example hepatocytes have different functions depending on oxygen concentration based upon their location on the portovenous axis, a phenomenon known as liver zonation (Burke and Tosh 2006; Davidson et al. 2012). Mathematical modelling of oxygen transport, and application of the mathematical models to the oxygen transport in laboratory settings (Davidson et al. 2012; Patzer 2004) as well as control of operating parameters (Shipley et al. 2011), is an important component of HFB *in vitro* model design.

Common design aspects and basic operation of HFBs

HFB configuration and operation

The configuration of a HFB provides a greatly increased surface area for cellular attachment and proliferation, in comparison to other bioreactor configurations. HFBs only require a volume that is 0.1% the capacity of a T-flask, or 0.5% the size of a stirred tank to grow an equivalent number of cells (Table 3) (Ellis et al. 2005). The culture parameters within the HFB must also be considered to ensure that they produce large cell yields and high viability without loss of phenotype; it is therefore very important that the physical, chemical and biological environment within the bioreactor is as close as possible to the *in vivo* environment and the HFB should be tailored to each cell type or types; attempts have been made to do this based on oxygen requirements for different cell types using computational fluid dynamics (Shipley et al. 2011). The semipermeable nature of the hollow fibre membrane is conducive to selective diffusion between media flowing through the fibre lumen and cells in the ECS, and the flux of media across the membrane can be prescribed based on membrane and bioreactor physical properties (Shipley et al. 2010). By culturing the cells in the ECS, shear stresses are decoupled from the bulk media flow in the lumen thus preventing cell damage, detachment from the culture substrate and undesirable shear stress responses. It should be noted however that a second media stream can be passed through the ECS if desired. Figure 2 shows several different configurations of HFBs. The important parameters to be controlled are the temperature, the flow rate of the media through the lumen, pH, the pressure differentials across the bioreactor, and dissolved oxygen, nutrient, waste product and metabolite concentrations and residence times. Other properties intrinsic to the fibre itself are also important to consider. For example, when culturing a desired cell number a bundle of fibres of a suitable length and diameter are necessary to provide the correct surface area for growth.

TABLE 3 PLACED HERE

FIGURE 2 PLACED HERE

Hollow fibre membrane fabrication and properties

The macroarchitecture of the hollow fibre membrane provides a highly permeable, minimally resistant

181 barrier that acts as a scaffold for adherent cells. The hollow fibre membranes used in HFBs for TE-
182 apps are usually made from a polymer, the fibre being fabricated using dry-wet or wet-wet spinning
183 (Ellis and Chaudhuri 2007). This produces a porous fibre with a hollow core, the lumen, through
184 which cell medium can flow. Structural, mechanical and topographical factors are dependent on the
185 manufacture of the fibre itself, including the type of polymer used, the solvent and nonsolvent
186 selection, the phase inversion process it has undergone, and any coating applied (Ellis and Chaudhuri
187 2007). For example, pore size can be modified by altering the initial casting dope solution (Ellis and
188 Chaudhuri 2008) to allow the selective passage of specific cellular products through the porous
189 polymer matrix based on their molecular weight. Careful selection of fibre fabrication conditions,
190 alongside the selected operating conditions, ensures good mass transfer of nutrients and oxygen
191 throughout the construct.

192 The hollow fibre biomaterial should also be biocompatible. Whether the surface is a suitable
193 environment for cell adherence is further influenced by several factors; *in vivo* this is achieved
194 through interaction between cell adhesion receptors such as integrins and the ECM. In the *in vitro*
195 setting, these interactions can be affected by the surface energy and topography of the biomaterial
196 surface (De Bartolo et al. 2002). A hydrophilic surface is more conducive to cell attachment due to the
197 ability for proteins within culture media serum to adsorb on to the biomaterial. Modification of the
198 biomaterial surface to mediate the biochemical signalling required for cell-matrix interactions can be
199 achieved through surface treatment, such as plasma treatment for the addition of functional groups to
200 increase hydrophilicity (Jacobs et al. 2012), or surface grafting of bioactive molecules, thus allowing
201 interaction between the cells and the added molecules rather than the polymer surface (Bellis 2011).
202 Alternatively, the ECS can also be filled with a gel to mimic the ECM. Immobilisation of cells in
203 sodium alginate has previously shown increased induction of vasculogenesis of human embryoid
204 bodies from human embryonic stem cells when compared to static or rotating bioreactor setups
205 (Gerecht-Nir et al. 2004). In addition, the use of alginate to immobilise primary porcine pancreatic
206 cells in a HFB setup demonstrated increased intracellular insulin compared to suspension cultures
207 (Hoesli et al. 2009).

The exact setup and operation of the HFB clearly depends on the tissue and the application, however there are a number of common considerations for their use. Figure 3 presents a generalised flow chart for cell culture in HFBs.

FIGURE 3 PLACED HERE

The Design and Application of Commercially-Available HFBs

Due to the advantages of growing cells in 3D structures, various research groups have strived to develop their own HFB systems. Others have developed HFBs into commercial brands, providing a variety of products with dimensions, separation properties and material types to suit numerous laboratory-testing applications. Some of the companies who sell bench scale HFBs are Fibercell Systems, Spectrum Labs, Terumo BCT and Eurotechnologies. The equipment provided by these three companies has been used in a small number of published articles for physical experimentation (FiberCell) (Usuludin et al. 2012) and used as a base for mathematical modelling (Spectrum Labs) (Chen and Palmer 2009).

Fibercell primarily produce hollow fibres made from polysulfone with the surface areas between 75 cm² and 2.5 m² with increasing ECS volume of 12 ml to 150 ml and a 50% packing density within a reactor housing made from glass. The additional surface area allows a greater number of cells to grow on and within the fibres, a maximum of 10⁹ – 10¹¹ over the range of HFB sizes. Molecular weight cut off (MWCO) ranges from 5 kD and 0.1µm and flow rates up to 200 ml min⁻¹ can be applied. This system is advertised to produce monoclonal antibodies and secreted proteins in high concentrations, to expand lymphocytes and endothelial cells, and to be used for *in vitro* toxicology tests (FiberCell 2014).

The HFBs sold by Spectrum Labs (brand name ‘Cellmax’) offer a wider range of materials: polysulfone, polypropylene, polyethylene, and regenerated cellulose. It recommends the most suitable polymer depending on the application: hollow fibres made from polysulfone if required to collect

secreted cell products, or made from either polypropylene or polyethylene for experimentation on cellular adhesion and gas diffusion (Spectrum Laboratories 2012). Pore sizes between 10 kD and 0.5 μm are available, and their HFBs allow a flow rate between 5-120 ml min^{-1} through the lumen of fibres with Reynolds numbers of less than 10 and velocities of 10^{-4} - 10^{-2} ms^{-1} depending on membrane size. Side ports are also included in this system to allow for a secondary flow through the ECS if required.

It could be argued that the presence of market leaders in lab scale HFB systems could allow parallels to be drawn between different research groups who use the same commercially available equipment, providing some sort of standard by which data could be compared. However in the process of writing this review only a handful of publications have actually used commercial HFB products, with many groups opting to make their own hollow fibres. If it can be demonstrated that a commercial HFB system could be constructed from materials of a known standard, and built using automated manufacturing techniques, a commercial system may prove advantageous for larger collaborative research projects and clinical utility to ensure consistency.

Theoretical Promises versus Actual Success and Current Issues with HFBs

The use of the commercial systems outlined above has been documented in journal articles, allowing data to be generated to check the claims reported in the catalogues of their manufacturers. A HFB cartridge purchased from Fibercell Systems was used (model C2011) to grow a co-culture of stromal and erythroleukaemia cells, of which 4.4×10^8 were successfully harvested from the HFB (Usuludin et al. 2012). This is almost an order of magnitude less than the advertised maximum cell number of 10^9 . The authors describe how a complete cell harvest was not achievable because some cells remained trapped between fibres, an issue which would arise in any tightly packed HFB. This harvesting issue of course is not a problem for hollow fibre membrane constructs designed for implantation.

The hollow fibre construct can also be a disadvantage because it does not allow the direct real time

visual inspection of cellular growth within the porous hollow fibre network, instead resorting to more indirect methods such as mass balances on gas exchange and nutrient uptake. One study comparing the performance of a commercially available HFB called the ‘Quantum Cell Expansion System’ (from Terumo BCT) with a static T-flask control for a modified human embryonic stem cell (hESC) line showed that despite achieving a larger cell count whilst utilising an equivalent of 15% of the T-flask growth medium, the HFB system achieved a lower cell viability (93-94%) and a lower cell density (18,000-34,000 cells cm⁻²) than the control (99%, 190,000 cells cm⁻²) (Roberts et al. 2012). The viability of the cells in the HFB was 93.5%, identical to that advertised by the manufacturer when growing Mesenchymal Stem Cells (MSC) (Nguyen et al. 2012). This level of viability was linked to longer exposure to lactate which was present in the HFB in higher concentrations at lower flow rates, causing moderate acidic conditions which has been shown to affect hESC growth (Chen and Palmer 2010). Increased flow rates through the reactor should mitigate stagnant conditions occurring. However this would need to be balanced with ensuring the subsequent high shear rates do not strip the cells from their scaffold (Titmarsh et al. 2011), or other modifications such as pore size and porosity.

In a more general sense, bioreactors typically fail to meet cell number and functional requirements because they provide unsuitable conditions for either the initial cell attachment or for the subsequent cell expansion. They are also much less sophisticated than the conditions found *in vivo*, with some aspects being much too elaborate for a bioreactor to control.

Conclusion

It is apparent from the studies reviewed here that the versatility of HFB design and their ability to expand a variety of cell types bodes well for their application in cell therapies, where mass production of cells is required for regular clinical use, and *in vitro* models, to reduce reliance upon animal experimentation. However, further study is required in both the understanding of the cellular interactions with the bioreactor and subsequent modification of the culture environment to ensure that there is homogeneity in the cell population. It is undisputable that HFBs provide the highest

theoretical culture efficiency based on surface area to volume ratio. HFBs are scalable and applicable to the culture of any cell type although are more suited to adherent cells and those from vascularised tissues. The product can be a population of cells removed by trypsin, or a single solid construct removed in its entirety from the module. A number of commercial HFBs are available although there is no standard operating procedure and optimal operation has not yet been achieved. The design and operation is specific to the cell type and end-use, and all aspects from hollow fibre material to pressure gradients and flow configuration need to be considered. HFBs have been successfully used for a range of tissues and this review suggests there is considerable interest and reason in continuing to explore and optimise their application for tissue engineering.

References

- Bellis SL. (2011). Advantages of RGD peptides for directing cell association with biomaterials. *Biomaterials* 32:4205-4210.
- Bernstein HS, Srivastava D. (2012). Stem cell therapy for cardiac disease. *Pediatr. Res.* 71(4):491-499.
- Burke ZD, Tosh D. (2006). The Wnt/beta-catenin pathway: master regulator of liver zonation? *Bioessays* 28(11):1072-1077.
- Chen G, Palmer AF. (2009). Hemoglobin-Based Oxygen Carrier and Convection Enhanced Oxygen Transport in a Hollow Fiber Bioreactor. *Biotechnol. Bioeng.* 102(6):1603-1612.
- Chen G, Palmer AF. (2010). Hemoglobin Regulates the Metabolic, Synthetic, Detoxification, and Biotransformation Functions of Hepatoma Cells Cultured in a Hollow Fiber Bioreactor. *Tissue Eng. Part A* 16(10):3231-3240.

Davidson AJ, Ellis MJ, Chaudhuri JB. (2012). A theoretical approach to zonation in a bioartificial liver. *Biotechnol. Bioeng.* 109:234-243.

De Bartolo L, Morelli S, Bader A, Drioli E. (2002). Evaluation of cell behaviour related to physico-chemical properties of polymeric membranes to be used in bioartificial organs. *Biomaterials* 23:2485-97.

Ellis M, Jarman-Smith M, Chaudhuri JB. (2005). Bioreactor Systems for Tissue Engineering: A Four-Dimensional Challenge. In: Chaudhuri J, Al-Rubeai M, (ed) *Bioreactors for Tissue Engineering*, Springer, Netherlands, pp 1-18.

Ellis MJ, Chaudhuri JB. (2007). Poly(lactic-co-glycolic acid) Hollow Fibre Membranes for use as a Tissue Engineering Scaffold. *Biotechnol. Bioeng.* 96:177-187.

Ellis MJ, Chaudhuri JB. (2008). Human bone derived cell culture on PLGA flat sheet membranes of different lactide : glycolide ratio. *Biotechnol. Bioeng.* 101(2):369-377.

FiberCell. (2014). Hollow fiber bioreactors and related products.
http://www.nbsbio.co.uk/downloads/fibercell_brochure.pdf . Accessed 20 May 2014

Gautier A, Ould-Dris A, Dufresne M, Paullier P, Von Harten B, Lemke H-D, Legallais C. (2009). Hollow fiber bioartificial liver: Physical and biological characterization with C3A cells. *Journal of Membrane Science* 341:203-213.

Gerecht-Nir S, Cohen S, Ziskind A, Itskovitz-Eldor J. (2004). Three-dimensional porous alginate scaffolds provide a conducive environment for generation of well-vascularized embryoid bodies from human embryonic stem cells. *Biotechnol. Bioeng.* 88(3):313-320.

Grek CL, Newton DA, Qiu YZ, Wen XJ, Spyropoulos DD, Baatz JE. (2009). Characterization of alveolar epithelial cells cultured in semipermeable hollow fibers. *Experimental Lung Research* 35(2):155-174.

330 Gundersen SI, Chen G, Powell HM, Palmer AF. (2010). Hemoglobin Regulates the Metabolic and
 331 Synthetic Function of Rat Insulinoma Cells Cultured in a Hollow Fiber Bioreactor.
 332 Biotechnol. Bioeng. 107(3):582-592.

333 Hoesli CA, Luu M, Piret JM. (2009). A Novel Alginate Hollow Fiber Bioreactor Process for Cellular
 334 Therapy Applications. Biotechnol. Prog. 25(6):1740-1751.

335 Jacobs T, Morent R, Geyter N, Dubrue P, Leys C. (2012). Plasma Surface Modification of
 336 Biomedical Polymers: Influence on Cell-Material Interaction. Plasma Chemistry and Plasma
 337 Processing 32:1039-1073.

338 Nguyen K, Brecheisen BS, Peters R, Startz T, Vang B, Baila S. (2012). Automated Expansion of
 339 Human Mesenchymal Stem Cells from Precultured Cells Using the Quantum Cell Expansion
 340 System. Online: Terumo BCT.

341 Niemeyer P, Fechner K, Milz S, Richter W, Suedkamp NP, Mehlhorn AT, Pearce S, Kasten P. (2010).
 342 Comparison of mesenchymal stem cells from bone marrow and adipose tissue for bone
 343 regeneration in a critical size defect of the sheep tibia and the influence of platelet-rich
 344 plasma. Biomaterials 31:3572-3579.

345 Nold P, Brendel C, Neubauer A, Bein G, Hackstein H. (2013). Good manufacturing practice-
 346 compliant animal-free expansion of human bone marrow derived mesenchymal stroma cells
 347 in a closed hollow-fiber-based bioreactor. Biochemical and Biophysical Research
 348 Communications 430:325-230.

349 Oh HI, Ye SH, Johnson CA, Woolley JR, Federspiel WJ, Wagner WR. (2010). Hemocompatibility
 350 Assessment of Carbonic Anhydrase Modified Hollow Fiber Membranes for Artificial Lungs.
 351 Artificial Organs 34:439-442.

352 Oo ZY, Deng RS, Hui M, Ni M, Kandasamy K, Bin Ibrahim MS, Ying JY, Zink D. (2011). The
 353 performance of primary human renal cells in hollow fiber bioreactors for bioartificial kidneys.
 354 *Biomaterials* 32:8806-8815.

355 Ott M, Ballermann B. (1995). Shear stress-conditioned, endothelial cell-seeded vascular grafts:
 356 improved cell adherence in response to in vitro shear stress. *Surgery* 117:334-339.

357 Patzer JF. (2004). Oxygen consumption in a hollow fiber bioartificial liver-revisited. *Artificial Organs*
 358 28(1):83-98.

359 Roberts I, Baila S, Rice RB, Janssens ME, Nguyen K, Moens N, Ruban L, Hernandez D, Coffey P,
 360 Mason C. (2012). Scale-up of human embryonic stem cell culture using a hollow fibre
 361 bioreactor. *Biotechnol. Lett.* 34(12):2307-2315.

362 Seliktar D. (2012). Designing Cell-Compatible Hydrogels for Biomedical Applications. *Science*
 363 336:1124-1128.

364 Shin SR, Jung SM, Zalabany M, Kim K, Zorlutuna P, Kim SB, Nikkhah M, Khabiry M, Azize M,
 365 Kong J and others. (2013). Carbon-Nanotube-Embedded Hydrogel Sheets for Engineering
 366 Cardiac Constructs and Bioactuators. *Acs Nano* 7:2369-2380.

367 Shipley RJ, Davidson AJ, Chan K, Chaudhuri JB, Waters SL, Ellis MJ. (2011). A Strategy to
 368 Determine Operating Parameters in Tissue Engineering Hollow Fiber Bioreactors.
 369 *Biotechnol. Bioeng.* 108(6):1450-1461.

370 Shipley RJ, Waters SL, Ellis MJ. (2010). Definition and Validation of Operating Equations for
 371 Poly(Vinyl Alcohol)-Poly(Lactide-Co-Glycolide) Microfiltration Membrane-Scaffold
 372 Bioreactors. *Biotechnol. Bioeng.* 107(2):382-392.

373 Simaria AS, Hassan S, Varadaraju H, Rowley J, Warren K, Vanek P, Farid SS. (2014). Allogeneic
374 Cell Therapy Bioprocess Economics and Optimization: Single-Use Cell Expansion
375 Technologies. *Biotechnol. Bioeng.* 111(1):69-83.

376 Soardi CM, Spinato S, Zaffe D, Wang HL. (2011). Atrophic maxillary floor augmentation by
377 mineralized human bone allograft in sinuses of different size: an histologic and
378 histomorphometric analysis. *Clinical Oral Implants Research* 22:560-566.

379 Spectrum Laboratories . (2012). CELLMAX Hollow Fiber Bioreactors - A Low Cost Alternative to
380 Conventional Cell Culture Methods. [https://webshop.fishersci.com/webfiles/uk/web-](https://webshop.fishersci.com/webfiles/uk/web-docs/CELLMAX.PDF)
381 docs/CELLMAX.PDF . Accessed 20 May 2014

382 Sullivan JP, Gordon JE, Bou-Akl T, Matthew HW, Palmer AF. (2007). Enhanced oxygen delivery to
383 primary hepatocytes within a hollow fiber bioreactor facilitated via hemoglobin-based oxygen
384 carriers. *Artificial cells, blood substitutes, and immobilization biotechnology* 35(6):585-606.

385 Sun T, Jackson S, Haycock JW, MacNeil S. (2006). Culture of skin cells in 3D rather than 2D
386 improves their ability to survive exposure to cytotoxic agents. *Journal of Biotechnology*
387 122:372-381.

388 Titmarsh D, Hidalgo A, Turner J, Wolvetang E, Cooper-White J. (2011). Optimization of Flowrate for
389 Expansion of Human Embryonic Stem Cells in Perfusion Microbioreactors. *Biotechnol.*
390 *Bioeng.* 108(12):2894-2904.

391 Torres J, Tamimi F, Alkhraisat MH, Prados-Frutos JC, Rastikerdar E, Gbureck U, Barralet JE, Lopez-
392 Cabarcos E. (2011). Vertical bone augmentation with 3D-synthetic monetite blocks in the
393 rabbit calvaria. *Journal of Clinical Periodontology* 38:1147-1153.

394 Usuludin SBM, Cao X, Lim M. (2012). Co-culture of stromal and erythroleukemia cells in a perfused
395 hollow fiber bioreactor system as an in vitro bone marrow model for myeloid leukemia.
396 *Biotechnol. Bioeng.* 109(5):1248-1258.

397 Vermonden T, Censi R, Hennink WE. (2012). Hydrogels for Protein Delivery. Chemical Reviews
398 112:2853-2888.

399 Williams DJ, Thomas RJ, Hourd PC, Chandra A, Ratcliffe E, Liu Y, Rayment EA, Archer JR. (2012).
400 Precision manufacturing for clinical-quality regenerative medicines. Philos. Trans. R. Soc. A-
401 Math. Phys. Eng. Sci. 370(1973):3924-3949.

402 Yamazoe H, Iwata H. (2006). Efficient generation of dopaminergic neurons from mouse embryonic
403 stem cells enclosed in hollow fibers. Biomaterials 27:4871-4880.

404 Zeilinger K, Schreiter T, Darnell M, Soderdahl T, Lubberstedt M, Dillner B, Knobeloch D, Nussler
405 AK, Gerlach JC, Andersson TB. (2011). Scaling Down of a Clinical Three-Dimensional
406 Perfusion Multicompartment Hollow Fiber Liver Bioreactor Developed for Extracorporeal
407 Liver Support to an Analytical Scale Device Useful for Hepatic Pharmacological In Vitro
408 Studies. Tissue Eng. Part C-Methods 17(5):549-556.

409 Zhang S, Liu T, Chen L, Ren M, Zhang B, Wang Z, Wang Y. (2012). Bifunctional polyethersulfone
410 hollow fiber with a porous, single-layer skin for use as a bioartificial liver bioreactor. Journal
411 of Materials Science Materials in Medicine 23:2001-2011.

412 Zhou X, Rowe RG, Hiraoka N, George JP, Wirtz D, Mosher DF, Virtanen I, Chernousov Ma, Weiss
413 SJ. (2008). Fibronectin fibrillogenesis regulates three-dimensional neovessel formation.
414 Genes & Development 22:1231-1243.

415

416

417

418

419 **Table 1** Cellular expansion using a HFB system

Cell	Type	Seeding		Expanded					References
		Number (cells)	Density (cells cm ⁻²)	Number (cells)	Density (cells cm ⁻²)	Fold increase	Visual depiction	Other analysis (e.g. biochemical)	
Lymphocyte	Human (primary tumour infiltrating)	1 x 10 ⁹	-	1 x 10 ¹¹ (dose reached)	-	-	-	Increased lactate (14d)	(Malone et al. 2001)
	Human (primary)	1.92 x 10 ⁸	-	-	-	-	-	Increased glucose uptake and lactate (8d)	(Curcio et al. 2012)
Embryonic stem cell	Human (Shef3)	6 x 10 ⁷	~ 3 x 10 ³	3.83 x 10 ⁹ (8d)	1.8 x 10 ⁴	-	-	Increased lactate	(Roberts et al. 2012)
				7.08 x 10 ⁹ (8d)	3.4 x 10 ⁴	-	-	(52h)	
Mesenchymal stem cell	Human (primary bone marrow)	2 x 10 ⁶	-	1.87 x 10 ⁷ (6d)	-	9.4	-	Increased glucose uptake and lactate (25d)	(Nold et al. 2013)
		3.5 x 10 ⁶	-	5 x 10 ⁷ (11d)	-	14.2	-		
		5 x 10 ⁶	-	9.8 x 10 ⁷ (13d)	-	20	-		
		7.6 x 10 ⁶	-	1.72 x 10 ⁷ (13d)	-	2.3	-	Increased DNA concentration (120h, 168h)	(Morgan et al. 2007)
		-	5 x 10 ³	-	-	25 (DNA concentration)	-		
Embryonic liver cell	Rat (RLC-18)	-	1 x 10 ⁴	-	-	1.97 (14d)	SEM (8d, 14d)	-	(Salerno et al. 2013)
Bone marrow stromal cell	Human (HS-5)	1 x 10 ⁸	4.76 x 10 ⁴	4.42 x 10 ⁸ (28d)	2.11 x 10 ⁵	-	-	Increased glucose uptake and protein concentration (28d)	(Usuludin et al. 2012)
Haematopoietic cell	Human (K562 co-culture with HS-5)	5 x 10 ⁵	-	-	-	3130 (14d)	-	-	
Adipose stem cell	Human (primary)	-	1 x 10 ⁵	-	-	-	Live-dead stain (3d, 7d)	Increased DNA concentration (1d, 3d, 7d)	(Diban et al. 2013)

420

421

422

423

424 **Table 2** Cellular differentiation using a HFB system

Cell	Type	Differentiated Cell	References
Haematopoietic stem cell	Human	Neutrophil	(Housler et al. 2012)
		Erythrocyte	
		Lymphocyte	
Embryonic stem cell	Mouse	Dopaminergic neuron	(Yamazoe and Iwata 2006)
		Hepatocyte	(Amimoto et al. 2011)
Induced pluripotent stem cell	Mouse	Hepatocyte	(Amimoto et al. 2011)
Mesenchymal stem cell	Sheep	Osteoblast	(De Napoli et al. 2011)
Embryonic liver cell	Rat	Hepatocyte	(Salerno et al. 2013)

425

426

427

428

429

430

431

432

433

434

435

436

437

438

439 **Table 3** Bioreactor design configurations and their capacities (Ellis et al. 2005).

Configuration	Media change	Mixing conditions	Tissue development	Culture dimensions	Size to grow an organ
Tissue culture flask	Batch	Poorly mixed	2D sheet	290 cm ² L ⁻¹ 1 x 10 ⁵ cells ml ⁻¹	10-1000 L
		No shear			
		Diffusion			
Stirred tank	Batch or continuous	Well mixed	2D or 3D	2800 cm ² L ⁻¹ 5 x 10 ⁵ cells ml ⁻¹	2-200 L
		Shear			
		Convection			
Packed beds	Continuous feed (perfusion)	Well mixed	3D	18,000 cm ² L ⁻¹ 2.5 x 10 ⁶ cells ml ⁻¹	0.4-40L
		Shear			
		Convection			
Fluidised bed	Continuous feed (perfusion)	Well mixed	3D	25,000-70,000 cm ² L ⁻¹ 5-6 x 10 ⁶ cells ml ⁻¹	0.2-20L
		Shear			
		Convection			
Membrane bioreactors	Continuous feed	Well mixed	3D	100,000-200,000 cm ² L ⁻¹ 2 x 10 ⁸ cells ml ⁻¹	0.05-0.5L
		No Shear or Shear			
		Convection and diffusion			

440

441

442

443

444

445

446

447

448

FIGURE LEGENDS

Figure 1 – Cell attachment and growth in a hollow fibre membrane. Cells can be seeded and consequently cultured on the lumen surface or the external surface of the membrane wall, or encapsulated in a gel in the extracapillary space. Cells could be encapsulated within the fibre wall itself, or allow migration if the pores are large enough, however such an approach is not covered in this review. Typical fibre outer diameter ranges between 500 – 1000 μm with a wall thickness of 200 μm . Figure not to scale.

Figure 2 – The different operational configurations of a hollow fibre bioreactor. A-D have retentate streams, the permeate flux can be prescribed by applying back pressure on the retentate stream; E-H are ‘dead-end’ with the retentate stream shut off (H is of no use in practice but shown for completeness); (I) Starling flow for which the extracapillary ports are shut off. A, C, E, G & I show co-current configurations, and B, D, F & H show counter current configurations.

Figure 3 – Common steps for performing cell culture in a hollow fibre bioreactor.

Figure 1

489 **Figure 2**

490

491

492

493

494 **Figure 3**

495

496